

## 36" FREEZER COLUMN WITH SOLID STAINLESS STEEL DOOR

### TR-36FRZ-R/L-SS-A

TR-36FRZ-R-SS-A (Right hinged)

TR-36FRZ-L-SS-A (Left hinged)

#### FEATURES

- Balanced, forced-air refrigeration system enables proper airflow and even temperature throughout to keep food fresh.
- Industry exclusive, 300-series stainless steel interior and exterior.
- All stainless steel, beautifully crafted proud hinges pass True's rigorous one million door opening test.
- Beautifully crafted solid stainless steel door with 120° stay-open feature and ergonomically designed, robust, tubular handle.
- Commercially inspired lift-up grill on top of the unit with toe kick that complements the look of True's undercounter units.
- Ramp-up, showcase interior LED lighting provides amazing illumination throughout.
- Intuitive True Precision® Control and readout provides digital accuracy and easy operation.
- Temperature as low as -4°F.

#### ORGANIZATION

- 3 adjustable/removable electropolished stainless steel wire shelves.
- 1 fixed electropolished stainless steel wire shelves.
- 3 full-extension, soft-close wire bins.

#### BUILD YOUR TRUE

Customize your True with a variety of finish and hardware options at [true-residential.com/custom](http://true-residential.com/custom).



TR-36FRZ-L-SS-A

#### SPECIFICATIONS

Dimensions (w x h x d) 36" x 84" x 24"

Cutout Dimensions (w x h x d)

Flush Opening 36¼" x 84¼" x 26"

Standard Opening 35¾" x 84¼" x 24"

Capacity (cu. ft.) 19.1

Temperature Range -4°F – 4°F

Weight (lbs.) 615

Voltage 115/60/1



Amps 2


Annual Energy Consumption (kwh) 466

Power Cord Length (ft.) 9

Energy Star Rated Yes

# 36" FREEZER COLUMN WITH SOLID STAINLESS STEEL DOOR

## TR-36FRZ-R/L-SS-A




### OPENING DIMENSIONS

#### FLUSH OPENING

WIDTH	HEIGHT	DEPTH
36 1/4"	84 1/4"	26"

#### STANDARD OPENING

WIDTH	HEIGHT	DEPTH
35 3/4"	84 1/4"	24"



### MODEL OPTIONS

MODEL	FINISH
TR-36FRZ-R-SS-A	Stainless solid door right-hinged
TR-36FRZ-L-SS-A	Stainless solid door left-hinged

### ACCESSORIES (OPTIONAL)

- Joining kit
- Side panel(s)
- Full size anti-condensation pad

### WARRANTY

- 3 year full (parts & labor)
- 6 year sealed system (parts & labor)
- 7-12 year (parts only – sealed system on registered products)